

PIPELINE HEATER PACKAGES

- Use to heat the gas upstream of pressure regulators and measurement facilities
- Indoor or outdoor installation
- Pipe sizes - 2" through 20" (contact factory for larger sizes)
- Simple field installation
- Stainless steel construction
- Over 50 years of field proven reliability
- Contact factory for correct sizing.

PIPELINE HEATER SPECIFICATIONS

HEATER MODEL	PIPE SIZE	BTUH INPUT
*1-6-24	2"	6,000
2-6-24	2", 3", 4"	12,000
2-12-24	4", 6", 8"	24,000
2-12-36	4", 6", 8", 10"	36,000
2-12-48	4", 6", 8", 10"	48,000
2-12-60	4", 6", 8", 10"	60,000
2-12-72	4", 6", 8", 10"	36,000
2-18-36	4", 6", 8", 10"	56,000
2-18-48	4", 6", 8", 10"	74,000
2-18-60	4" - 20"	90,000
2-24-48	4" - 20"	100,000
2-24-60	4" - 20"	120,000
2-24-72	4" - 20"	144,000

*Stainless steel reflector replaces one heater.
Pipeline Heater Package Dimensions available upon request.

LARGER PIPELINE HEATER PACKAGES AVAILABLE UPON REQUEST

- Standard model heaters are for use in non-hazardous locations
- FM model heaters for use in Class 1, Division 2, ,Group D locations
- CSA model heaters for use in Class 1, Division 1 and 2, Group D locations
- Specify start-up Voltage - 12V - 120V - 240V - 480V
- Specify fuel - natural, L.P. (propane),
or butane gas
- Accessories -
Fuel gas manifold and regulator
Explosion proof junction boxes

